



Standard Exchange Cart

Product Information

Application:

Standard Exchange Carts are a convenient way to transfer molds either before or after the casting process, from one line of conveyor to another.

Description:

The Standard Exchange Cart features heavy duty steel construction, galvanized steel wheelway utilizing steel skate conveyor wheels, easy rolling v-groove wheels, and durable Gruber blue powdercoating for easy cleanup and protection. The Standard Exchange cart is available in either 10 foot or 12 foot lengths.



Tilt and Rotate Cart

Product Information

Application:

Tilt and Rotate carts are specifically designed for the transfer of molds through the gelcoat application. These carts have special features built in to simplify the gelcoating process.

Description:

Tilt and Rotate carts feature heavy duty steel construction, galvanized steel wheelway with steel skate conveyor wheel, easy rolling v groove wheels, pneumatic operation for hazardous areas, heavy duty steel rotate plate, and durable Gruber blue powdercoating for easy cleanup and protection. Tilt and Rotate carts are available in three different configurations, 10 foot and 12 foot lengths.



Product Range:

Tilt and Rotate Cart

0830610	TILT ONLY GELCOAT CART, 10'
0830612	ROTATE ONLY GELCOAT CART, 10'
0830612F	ROTATE GELCOAT CART FINISH, 10'
0831413	TILT ONLY CART, 10' NO WHEELWAY
083160	TILT/ROTATE GELCOAT CART, 10'
0830611	TILT ONLY GELCOAT CART, 12'
0830613	ROTATE ONLY GELCOAT CART, 12'
0830613F	ROTATE GELCOAT CART FINISH, 12'
083161	TILT/ROTATE GELCOAT CART, 12'
111382	TILT/ROTATE CART HOSE REEL

110081	JOY PENDANT STATION-UP/DN
Standard Exchange Cart	
083078	STANDARD EXCHANGE CART 10'
083079	STANDARD EXCHANGE CART 12'
0830791	DOUBLE WIDE STANDARD EXCHANGE CART 13'
083079D	DOUBLE WIDE STANDARD EXCHANGE CART

Accessories

083087	CART TRACK 10'
083090	STANDARD RIGID V-GROOVE CASTER
110039	STANDARD STEEL W/W WHEEL W/N&B
162390	CART TRACK STOPS

Specifications:

Standard Exchange Cart Dimensions:

- Frame
 - Height: 2'-4" (28") to top of wheelway
 - Width: 2'-0" (24")
 - Length: 10'-0" (120") to 12'-0" (144")
 - Wheel Depth: 3'-0" (36")
 - Wheel Base: 6'-0" (72")
- Wheelway
 - Width: 20 1/8" wheel center to wheel center

Tilt and Rotate Cart Dimensions:

- Frame
 - Height: 2'-4" (28") to top of wheelway
 - Width: 21 1/2"

Length: 10'-0" (120") to 12'-0" (144")
 Wheel depth: 3'-0" (36")
 Wheel base: 6'-0" (72")

- Wheelway
 - Width: 20 1/8" wheel center to wheel center
- Tilt
 - Lever operated, pneumatic cylinder driven for a maximum of 40° of forward tilt.
- Rotate
 - Lever operated, pneumatic cylinder driven for 4" of lift off of the wheelway enabling 360° of rotation.



25636 Ave. Stanford Valencia CA, 91355 USA
 Tel. 800 257-4070; 661 257-4060
 Fax 800 247-8237; 661 257-4791
 E-mail sales@gruber-systems.com
 www.gruber-systems.com